

DT-OM

AquaPoint™ Sealed Industrial Optical Mouse

Constructed using the same rugged materials that go into the entire line of iKey peripherals, the NEMA 4X AquaPoint™ industrial pointing device features a sealed industrial silicone overlay and robust polycarbonate frame. Its reliable optical technology allows it to function on most surfaces, while its smooth-surfaced buttons make the unit easy to clean. Solid-state engineering ensures the AquaPoint™ a long operating life, making the new device the ideal alternative to the office-grade mice that are so commonly replaced in harsh environment settings. The AquaPoint™ is available in either USB or PS/2.

Buy now through iKeyDirect.com to receive free shipping on this



Technical Specifications

Certifications

NEMA 4X
UL60950, FCC Part 15 Class B

Key Switch

MATERIAL: Industrial silicone rubber
LIFE: 10 million cycles
TRAVEL: 0.055
ACTUATION FORCE: 200g (+/- 20g)
FEEDBACK: Tactile with mechanical snap

Power

5V@ 50 ma (from mouse conn. port)

Temperature Range

STORAGE: -40C to +90C
OPERATING: -40C to +60C

Humidity

100%

Shock

3x11 ms pulses of 50g on each of 3 axes

Vibration

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2 kHz
DURATION OF TEST PER AXIS: 3 hours

Flammability

PRINTED CIRCUIT BOARD: 94 VO
SILICONE OVERLAY: 94 HB
INTERFACE CABLE: 94 VO

Weight

0.4 lbs (0.18 kg)
1 lb (shipping)

Dimensions

2.58" x 5" x 1.56" (w-h-d)
65.5mm x 127mm x 39.6mm

Cable

LENGTH: 6 feet
DESIGN: PS/2 or USB cable

Compatibility

USB: All Windows and Macintosh OS

Warranty

1 year limited warranty

Model Numbers

DT-OM-USB: With USB cable

Features and Benefits

- USB configurations available
- Solid State, Optical Tracking Technology
- 2.58" x 5" x 1.56" (w-h-d)
- Comfortable, Ergonomic Design
- Smooth-Surface Buttons