

RDC-1535

Rackdrawer Keyboard

This rackdrawer unit is a standardized desktop keyboard with the benefits of "click-feel" keys and a ruggedized HulaPoint™ pointing device. Standard size units have 14-inch rails (15-inch-deep drawer) and come with chrome handle or pull slot options. Larger size units have 16-inch rails (17-inch drawer) and come with T-handle or locking T-handle options. The drawers have a CRS steel construction, which is coated with black epoxy paint and chrome-plated, ball-bearing slides. (Model shown in photo has a chrome handle, part number RDC-1535-H).



Technical Specifications

Certifications

UL60950, FCC Part 15 Class B

Key Switch

MATERIAL: Industrial silicone rubber
LIFE: 10 million cycles
TRAVEL: 0.055
ACTUATION FORCE: 200g (+/- 20g)
FEEDBACK: Tactile with mechanical snap

Power

KEYBOARD: 5V@ 10 ma (from CPU port)
HULAPoint: 5V@ 10 ma (from mouse conn. port)

Temperature Range

STORAGE: -40C to +90C
OPERATING: -40C to +60C

Humidity

100%

Shock

3x11 ms pulses of 50g on each of 3 axes

Vibration

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2 kHz
DURATION OF TEST PER AXIS: 3 hours

Weight

16 lbs (7.36 kg)

Dimensions

Pull Slot/Chrome Handle: 19" x 15" x 1U (1.75")
(w-h-d)
482.6mm x 381mm x 44.5mm
T-Handle: 19" x 17" x 1U (1.75")
482.6mm x 431.8mm x 44.5mm

Compatibility

PS/2: All Windows Operating Systems

Warranty

1 year limited warranty

Model Numbers

RDC-1535-PS2: With PS/2 cable
RDC-1535-USB: With USB cable
RDC-1535-16-T-xxx: 16" Rails T-handle
RDC-1535-16-RK-xxx: 16" Rails T-handle Key

Features and Benefits

- 19" x 15" x 1.75" (w-h-d)
- AT/Serial and PS/2 configurations available
- Integrated HulaPoint™ Pointing Device
- Slide Load Rating: 130 Lbs/Pair