



**FOR IMMEDIATE RELEASE**

June 2, 2010

**FOR INFORMATION:**

Halley Cade, 512-837-0283

**iKey launches line of ruggedized industrial displays**

**Austin, Texas** – iKey, the recognized leader in premium input devices, is proud to introduce its new line of robust industrial flat panel displays built for use in harsh environments.

“iKey has over 21 years of experience in providing companies around the world with rugged peripheral equipment,” Halley Cade, iKey Marketing Coordinator, said. “We are proud to put our expertise, value and quality into the new IK line of displays. We are now able to offer our customers a complete input and display solution that is able to withstand the demands of extremely harsh environments.”

The new line features slim-profile alloy panels that are resistant to dirt, dust, liquids and corrosives. The line includes several size options: the 15” IK-PDS-1502, the 17” IK-PDS-1703 and the 19” IK-PDS-1902. Each model is available with an optional resistive touchscreen. Prices start at \$1,095.

Built specifically for dirty or wet areas, the IK line has an IP65-rated front panel. Each model has an operating temperature of 0°C - 50°C, a storage temperature of -20°C - 60°C, and reliability of over 50,000 hours.

“The IK line is suited for our customers in food and beverage manufacturing, material handling, and industrial automation because of its robust



IK-PDS-1703 is an industrial flat panel built for use in harsh environments.

features,” Cade said. “Not only can it be sprayed down, but it can successfully operate in areas where normal systems may periodically fail due to debris and liquid in the air.”

The IK line is designed for easy integration into most applications. Each display is equipped for VESA mounting, panel-mounting, wall-mounting and wall-embedded installation.

	<b>IK-PDS-1502</b>	<b>IK-PDS-1703</b>	<b>IK-PDS-1902</b>
<b>Display Screen</b>	15" LCD	17" LCD	19" LCD
<b>Dimensions</b>	15.75"x11.81"x1.57"	16.18"x14.0"x2.17"	19.02"x14.84"x2.09"
<b>Net Weight</b>	10.9 lbs	15.65 lbs	14.33 lbs
<b>Brightness</b>	350 cd/m <sup>2</sup>	300 cd/m <sup>2</sup>	300 cd/m <sup>2</sup>
<b>Support Color</b>	16.2M colors (RGB 8-bit)	16.7M colors (RGB 6-bit)	16.7M colors (RGB 6-bit)
<b>Contrast Ratio</b>	700:1	800:1	1300:1
<b>Resolution</b>	1024x768	1280x1024	1280x1024
<b>Response Time</b>	8ms	5ms	8ms
<b>Relative Humidity</b>	5%-93%, 40° non-condensing	5%-95%, 40° non-condensing	5%-95%, 40° non-condensing
<b>Shock</b>	15g peak acceleration	10g peak acceleration	10g peak acceleration
<b>Vibration</b>	5-19Hz/1.0mm amplitude	5-17Hz/1.0mm amplitude	5-17Hz/1.0mm amplitude

For more information on iKey's rugged displays, and how they can integrate with your iKey keyboard, visit [www.ikey.com](http://www.ikey.com), or call (800) 866-6506.

**About iKey, Inc.:** iKey designs, manufactures and sells sealed, rugged and [custom keyboards](#) for industrial, kiosk, public safety, medical and military environments. All iKey products are designed to function in harsh conditions. A pioneer in its industry since 1989, iKey is known as an innovator of industrial computer peripherals.

**Contact:**  
**Halley Cade**  
(512) 837-0283  
[hcade@ikey.com](mailto:hcade@ikey.com)  
[www.ikey.com](http://www.ikey.com)