


AK-39

DATE	CHANGES	INTL	REV
01.26.09	Original	JB	1.00



KEY SWITCH

MATERIAL: Industrial Silicone Rubber
LIFE: Greater Than 10 Million Cycles
TRAVEL: 0.055 in.
ACTUATION FORCE: 8.11 oz. +/- 1.06oz (230g +/- 30g)
FEEDBACK: Tactile with Mechanical Snap

POWER

USB: 190mA@5V (from CPU port)

TEMPERATURE RANGE

STORAGE: -40°F to +167°F (-40°C to +75°C)
OPERATING: -40°F to +158°F (-40°C to +70°C)

HUMIDITY

100% Humidity Resistant

VIBRATION

POWER SPECTRAL DENSITY: .04g/HZ
FREQUENCY RANGE: 20Hz-2KHz
DURATION OF TEST PER AXIS: 3 hours

SHOCK

3 X 11 ms pulses of 50g on each of 3 axis

WEIGHT

0.50 lbs +/- 0.10 lbs (0.23 kg +/- 0.05 kg)

PROPRIETARY AND CONFIDENTIAL

SCALE: 1:1.25



iKey, Ltd.
 2621 Ridgpoint Dr. Suite 235
 Austin, Texas 78754

©2008 iKey, Ltd.
 Voice: (512) 837-0283
 Fax: (512) 927-8630

Part Number: AK-39
Drawing Title: AK-39-MKT

Drawing Number: MKT0173
Revision: 1.00

Sheet: 1 OF 1
Date: 01.26.09
JWB