



SLP-910

DATE	CHANGES	INTL	REV
04.24.24	Original	ADD	1.0



KEY SWITCH

MATERIAL: Epoxy Coated Industrial Silicone Rubber
 FACEPLATE MATERIAL: ABS/Polycarbonate
 LIFE: Greater Than 10 Million Cycles
 TRAVEL: 0.055 in.
 ACTUATION FORCE: 7.03 oz. +/- 0.70 oz (200g +/- 20g)
 FEEDBACK: Tactile with Mechanical Snap

POWER

PS2: KEYBOARD: 200mA@5V (from Keyboard port)
 USB: 200mA@5V (from CPU port)

TEMPERATURE RANGE

STORAGE: -40°F to +194°F (-40°C to +90°C)
 OPERATING: -40°F to +158°F (-40°C to +70°C)

HUMIDITY

100% Humidity Resistant

VIBRATION

POWER SPECTRAL DENSITY: .04g/HZ
 FREQUENCY RANGE: 20Hz-2Khz
 DURATION OF TEST PER AXIS: 3 hours

SHOCK

3 X 11 ms pulses of 50g on each of 3 axis

WEIGHT

1.75 lbs +/- 0.10 lbs (0.80 kg +/- 0.05 kg)

PROPRIETARY / CONFIDENTIAL

SCALE: 1:2



iKey, Ltd.
 2621 Ridgpoint Dr. Suite 235
 Austin, Texas 78754

©2024 iKey, Ltd.
 Voice: (512) 837-0283
 Fax: (512) 927-8530

Part Number: SLP-910

Drawing Title: SLP-910-MKT

Drawing Number: MKT0549


Revision: 1.0

Sheet: 1 OF 2

Date: 04.24.24

ADD

SLP-91 MOUNTING



PM BEZEL: ABS/Polycarbonate

PROPRIETARY / CONFIDENTIAL



iKey, Ltd.
2621 Ridgpoint Dr. Suite 235
Austin, Texas 78754

©2024 iKey, Ltd.
Voice: (512) 837-0283
Fax: (512) 927-8530

Part Number: SLP-910
Drawing Title: SLP-910-MKT

Drawing Number: MKT0549
Revision: 1.0

Sheet: 2 OF 2
Date: 04.24.24

ADD